

proxSafe®

Key Management & Smart Storage Systems

The intelligent management system for keys and equipment with comprehensive audit and reporting capabilities. Control who can have access to individual items and restrict when they can be taken. Keys, radios, test equipment, tools, laptops and much more can now be managed efficiently with increased accountability so you know where they are and who has them. The powerful software Commander Connect allows easy configuration and control of access rights, time profiles and the creation of individual reports. That way you stay in control at all times and make the best use of your equipment.

Compartment system for cases, notebooks, documents

proxSafe locker L is an electronic storing system for cases, notebooks, documents or other valuables. All items are stored in separate compartments. The columns consist of 4, 6 or 8 compartments and one service compartment for installation and emergency release. proxSafe locker systems are optimized for daily use. The design is smart and elegant, so the system can be installed in any architectural environment.

proxSafe locker L is operated with a proxSafe Terminal. After a user has been identified and has selected a compartment, the corresponding door will be unlocked. This is indicated by an LED. Also upon return of the contents the compartment is marked with an LED in order to guide the user to the right position. proxSafe locker L is equipped with automatic content monitoring. There is a proxCylinder or RFID reader in every compartment which identifies the contents certainly and reliably.

The built-in feature of fail-safe opening protects you from unauthorized access. Power failures are covered by a built-in backup-battery. All proxSafe housings are equipped with tamper contacts and 4 relays which can indicate various alarms via the network and locally.

Your benefits at a glance:

- **Power save mode with backup battery**
- **Fail-safe open**
- **Contactless technology, maintenance-free**
- **Convenient emergency opening**
- **4 outputs for local alarms**



locker L 4

locker L 6

locker L 8

Technical Data

Outer Dimensions WxHxD / Weight:	650 x 1920 x 550 mm / 200 kg
Inner Dimensions WxHxD:	
L 4 / 4 Compartments	523 x 397 x 530 mm
L 6 / 6 Compartments	523 x 260 x 530 mm
L 8 / 8 Compartments	523 x 192 x 530 mm
Service Compartment WxHxD:	523 x 133 x 530 mm
Material:	sheet steel 12.03 frame 2 mm doors 2 mm
Colour:	powder coated, frameDB 502, doors similar RAL 9006
Operating Temperature:	+5...+50 °C
Relative Humidity:	5...95 %, non-condensing
Power Requirement:	110...240 VAC
Frequency Compartment ID:	125 kHz
Backup Battery:	12 VDC / 2.3 Ah
Digital Output:	4x 30 VDC / 1 A for up to 16 alarms